

QUARTER FIBERGLASS VENDOR



WV-4000F-SS-QTR – Single Vendor
WV-4000F-SD-QTR – Dual Vendor

STANDARD

- Hand Laid Fiberglass Cabinet
- Single Price Vending Controller
- Quarter Acceptor W/Sold Out Coil – Single/Dual
- Triple 20” Slimline RO Prefilters
- 2” X 21” HF TFC RO Membrane – 100GPD @ 60PSI
- 75 Gallon Poly Storage Tank
- 3 GPM Delivery Pump – Single/Dual
- 1 GPM Sump Pump
- UV/Carbon Sterilizer – Single/Dual
- Liquid Fill PSI Gauges
- Three Quantity Vend Buttons – Single/Dual
- Totalizer Pulse Flow Meter – Single/Dual
- LED Credit/Program Display
- Relay RO Control System
- Relay Control Sump Pump System
- Dual T-Handle Door Locks
- Lighted Marquee
- Stainless Steel Bottle Shelves
- Stainless Steel Cash Box
- Stainless Steel Hardware
- Chlorine Test Valve
- TDS Test Valve
- Dual Dispense Nozzle

SYSTEM SPECIFICATIONS

Cabinet Size: 45”W X 34”D X 78”H
 Cabinet Weight: 560 LBS
 Water Inlet: ½” NPT
 Waste Outlet: ½” NPT
 Electrical: 120VAC – 5 AMPS
 Minimum Water: 60PSI @ 1 GPM

OPTIONS

400 GPD RO System
 800 GPD RO System
 2000 GPD RO System
 Ozone System
 Insulated Cabinet

For More Information: