



NAMA
LISTED

WALL MOUNT - RO PROCESSOR w/ 300 Gal. Storage Tank



WM-450-D

STANDARD

- 3' X 4' X 3/4" Plywood Backboard w/ 1/8" Plastic Overlay
- 10" BB Sediment RO Prefilter
- 10" BB Carbon Block RO Prefilter
- 2" X 21" HF TFC RO Membrane 450 GPD@ 150 PSI
- 1/4 HP RO Motor
- 40 GPH RO Pump
- 30 AMP RO Relay w/ Tank Floats
- Dual UV/Carbon Sterilizer
- Dual 3.3 GPM Delivery Pumps
- Low Pressure Sensor
- Chlorine Test Valve
- TDS Test Valve
- Installation Kit

SYSTEM SPECIFICATIONS

- SIZE: 3' X 4' For D Model
4' X 6' For Q Model
- WEIGHT: D Models -- 250 Lbs
Q Models -- 350 Lbs
- WATER INLET: 1/2" NPT
- WATER OUTLET: 1/2" NPT
- ELECTRICAL: 12 AMPS
- MINIMUM WATER: 1000-D 45 PSI @ 2 GPM
2000-D 45 PSI @ 4 GPM

MODELS

- **WM-450-D** 450 GPD RO With Dual Dispense
- **WM-1000-D** 1000 GPD RO With Dual Dispense
- **WM-2000-D** 2000 GPD RO With Dual Dispense
- **WM-1000-Q** 1000 GPD RO With Quad Dispense
- **WM-2000-Q** 2000 GPD RO With Quad Dispense